

UHF FM HANDHFI D TRANSCFIVER

DJ-FX446

C€0700⊕



BIKE! HIKE! WORK...and TALK!

This new UHF PMR446 transceiver packs a lot of performance into a super-compact body. The DJ-FX446 features clear, crisp audio with a compact antenna where portability comes first. Capable of operating PMR446 with full legal output, it is perfect for any application where instant short-range communications are necessary; keep in touch around the house, down the road, in a theme-park, shopping mall, exhibition hall, for business, factory, warehouse, outdoor sports, hunting, fishing...where you need to talk to someone, the DJ-FX446 is a brilliant cost-effective alternative to a mobile phone!

- Computer-programmable with free software downloadable from Alinco website (Optional ERW-8 interface cable required)
- Includes a long-life 3.7V 1000mAH Li-ion cell with powerful legal-limit TX output and clear, crisp 300mW Audio output
- Compact size 50W x 157H x 19D mm (with antenna)
- Weight approx. 90g inclusive of EBP-90 battery pack and
- Efficient ultra-compact antenna for better portability
- Scan functions
- 50 CTCSS tones and 105 DCS Tones
- Simple, easy-to-use interface and Back-lit, large LCD screen Includes VOX function, APO, Low Battery indication, Key lock function, Tone Call, and more!

Standard Accessories

- Belt Clip
- Handstrap
- EBP-90 Li-IO 3.7V 1000mAh **Battery** pack
- EDC-201 AC adapter



Optional Accessories

- FMF-61 Farphone Microphone (VOX capable)
- EME-24 Earphone Microphone
- EMS-60 Speaker-microphone
- ERW-8 Computer interface cable

Internal VOX is not usable with EME-24 and EMS-60



Specifications

Frequency range: 446.00625-446.09375 MHz (8 channels)

Output power: Max. 0.5W

CTCSS/DCS tones: 50 CTCSS / 105 DCS

Frequency stability: ±2.5ppm Rx Sensitivity : -9dBµ EMF Supply voltage: 3.7Vdc

Operating temperature: -20°C~+65°C Charging temperature : 0°C~40°C

Battery type: 1000mAH(Li-ion)

Dimensions: 50W x 157H x 19D mm (approx. with antenna)

Weight: approx, 90g with battery pack

Audio output: 300mW

Specifications may be changed without a preliminary announcement in connection with technical development. Standard accessory may vary. Please consult with your local dealer before purchase.

ALINCO, INC. Electronics Division

odoyabashi Dai-Bldg 13F, 4-4-9 Koraibashi, Chuo-ku, Osaka 541-0043 Japan Phone: 06-7636-2362 Fax: 06-6208-3802

www.alinco.com E-mail: export@alinco.co.jp

Authorized Dealer:

ALINCO FRANCE www.alinco.fr



Actual Size